

TS®54 TDR

Overview

Premium Voice, Data, and Video Telephone Test Set The innovative TS54 TDR (Time Domain Reflector) is perfect for voice, data and video technicians and communication service provider technicians who need a best-in-class test set combined with a powerful TDR and toner. Fluke Networks took the best telephone test set features and design and combined them into one. There's nothing else like the TS54 TDR on the market today. No longer will you need to carry a separate TDR, toner, pair identifier and butt-in test set—everything you need is in one newly redesigned and compact package. The TS54 delivers 20% more extreme weather protection with the latest advancements to our patented RainSafe™, DropSafe™ and DataSafe™ technology. This means the TS54 is weatherproof and rugged and able to butt in on live DSL lines to test POTS quality without crashing data service. DropSafe™ PRO – passed 20-foot drop test onto concrete RainSafe™ PRO – protection for extreme weather conditions DataSafe™ PRO – prevents disruption of data transmission on the line High-visibility keypad with glow-in-the-dark keys for any outside plant environment Extra-large, backlit LCD screen Familiar, cell phone-like menu and user interface Two-way, hands-free speakerphone Low battery and mute indication Optional headset



Features

TDR – find cable length measurement and locate faults on virtually all types of cable including twisted pair, coaxial, and parallel conductors
 Toner – five separate tones for fast and easy differentiation between multiple wire pairs
 SmartTone® – short the correct pair and tone changes for exact pair identification
 Additional key testing functions include:
 Data indication – warns when data is present on the line
 Voltage indication/measurement – identifies potential line problems
 Current (mA) indication/measurement – verifies sufficient line current
 Caller-ID with Call Waiting — verifies functional service
 DTMF Digit Grabbing — isolates faulty customer premise equipment
 Detects dial tone, places and receives calls
 Polarity



Extra-large, backlit LCD screen



Glow-in-the-dark keys for any outside plant environment

Specifications

Electrical	
Current range (Off-Hook)	10 mA to 100 mA
DC Resistance	
Off-Hook	150 Ω nominal
On-hook	3 M Ω
AC Impedance	
Off-hook	600 Ω nominal; 300 Hz to 3400 Hz
On-hook	120 k Ω ; 300 Hz to 3400 Hz
Headset impedance	32 Ω

Rotary Dial Output

Pulsing rate	10 pps \pm 1 pps
Break/make ratio	60/40
Interdigit interval	300 ms
Resistance during break	100 k Ω

DTMF Output

Tone frequency error	\pm 1.5% maximum
Tone level	-3 dBm combined (typical)
High versus low tone difference	2 dB \pm 2 dB

Speed Dialing

Memory capacity	9 speed dial memories of 23 digits, plus one last number redial memory
PBX pause duration	User programmable; default of 4 seconds
Hook flash duration	User programmable; default of 500 ms
Automatic shut-off duration	User programmable; default of 2 minutes

Voltage measurement

Range	4 V dc to 140 V dc
-------	--------------------

Current measurement

Range	0 mA to 100 mA
-------	----------------

TDR

Range	3,000 feet (914 m)
Accuracy	\pm 2 m \pm 5 %

SmartTone toner

Frequencies	Steady tone: 950 Hz Alternating tones: 950 Hz and 1480 Hz
Power	
Battery type	9 V alkaline battery
Physical	
Dimensions	8.3 in x 3.2 in x 2.6 in (211 mm x 81 mm x 66 mm)(without belt clip)
Weight	1.16 lb (0.53 kg) (without belt clip)
Water resistance	The test set is rain and moisture resistant

Environmental	
Temperature range	
Handset speech and dialing functions	-22°F to 140 °F (-30°C to 60°C)
LCD function	-13°F to 140°F (-25°C to 60°C)
Storage	-22°F to 150°F (-30°C to 66°C)
Altitude	To 10,000 ft. (3,000 m) max
Relative humidity	95% to 30°C 75% to 40°C 45% to 50°C 30% to 60°C
Safety	
Regulatory compliance	Complies with ANSI/ISA 82.02.01 (61010-1) 2004, CAN/ CSA-C22.2 No. 61010-1-04, UL 61010-1 (2004) and IEC 61010-1:2010 for measurement category I, 300 V dc maximum, pollution degree 2
Maximum transient voltage	1500 V
EMC	Complies with EMC EN61326-1

Notes: Specifications subject to change without notice.

Ordering Guide

Item Number	Description
TS54-A-09-TDR	Test Set + TDR, ABN with Piercing Pin
TS54-BANA	Test Set + TDR, 4 MM Banana, Extra-large Alligator Clips, Test Probe

Accessories Guide

Item Number	Description
BELTCLIP-TS	Belt Clip
LEAD-PIRC-PIN	Test Leads with Piercing Pin Clips
LEAD-CO-346A	Test Leads with a 346A Plug for the Central Office ¹
LEAD-ABN-PPIN	Test Leads with Angled Bed-of-Nails (ABN) and Piercing Pin Clips
LEAD-ALIG-CLP	Test Leads with Alligator Clips
LEAD-ABNPRJ11	Test Leads with an RJ-11 Plug, Angled Bed-of-Nails (ABN), and Piercing Pin Clips
TEST-LEAD-BANA-CLP	Test Leads with a 4 mm Banana Plug, Alligator Clips, and Test Probe
HEADSET-TS	Headset

1. When you use these test leads, the TDR accuracy specifications do not apply.

About Fluke Networks

Fluke Networks is the worldwide leader in certification, troubleshooting, and installation tools for professionals who install and maintain critical network cabling infrastructure. From installing the most advanced data centers to restoring service in the worst weather, our combination of legendary reliability and unmatched performance ensure jobs are done efficiently. The company's flagship products include the innovative LinkWare™ Live, the world's leading cloud-connected cable certification solution with over fourteen million results uploaded to date.

1-800-283-5853 (US & Canada)

1-425-446-5500 (International)

<http://www.flukenetworks.com>

Descriptions, information, and viability of the information contained in this document are subject to change without notice.

Revised: October 1, 2019 8:25 AM

Literature ID: 4107295B

© Fluke Networks 2018